

10/599273

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/001184

International filing date: 24 March 2005 (24.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0411434.4  
Filing date: 21 May 2004 (21.05.2004)

Date of receipt at the International Bureau: 18 May 2005 (18.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/GB2005/001184

GB05/1184



INVESTOR IN PEOPLE


The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed


*Andrew Gervy*

Dated

3 May 2005

# Patents Form 1/77

Patents Act 1977  
(R 1977)



24MAY04 E898004-3 D02835  
P01/7700 0.00-0411434.4 ACCOUNT CHA

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP9 1RH

1. Your reference

HE/P501790

21 MAY 2004

2. Patent application number

(The Patent Office will fill in this part)

0411434.4

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Hoover Limited  
Dragonparc  
Abercanaid  
Merthyr Tydfil  
Mid Glamorgan  
CF48 1PQ  
UNITED KINGDOM

5942/70001

4. Title of the invention

Vacuum Cleaner

5. Name of your agent (if you have one)

URQUHART-DYKES & LORD

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Three Trinity Court  
21-27 Newport Road  
CARDIFF  
CF24 0AA

8857328001

Patents ADP number (if you know it)

1644025

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

EP

04251833.2

29/03/2004

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	10	✓
Claim(s)	-	
Abstract	-	
Drawing(s)	4 + 4	Done

10. If you are also filing any of the following, state how many against each item.

Priority documents	-
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	-
Request for preliminary examination and search (Patents Form 9/77)	-
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	-

11.

I/We request the grant of a patent on the basis of this application.

Signature		Date
URQUHART-DYKES & LORD	21 May 2004	

12. Name and daytime telephone number of person to contact in the United Kingdom

Huw D D Evans

029 2048 7993

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

## Vacuum Cleaner

This invention relates to a vacuum cleaner.

Known vacuum cleaners are either of the so-called upright type or the so-called cylinder type. Upright vacuum cleaners comprise an upright portion pivotally connected at its  
5 lower end to a wheeled floor-engaging portion for partial rotation forwardly and rearwardly about a transverse axis. The upright portion encloses a motor/fan unit which draws air into a dust separation device through an inlet in the floor-engaging portion of the cleaner. A handle is provided at the upper end  
10 of the upright portion for manoeuvring the cleaner. A motor-driven rotating agitator brush is mounted across the inlet in the floor-engaging portion to beat and sweep the floor in the region of the airflow into the cleaner.

Cylinder vacuum cleaners comprise a body which encloses  
15 a motor/fan unit which draws air into a dust separation device through an elongate flexible hose. A plurality of tools are provided for fitting to the end of the hose.

Upright vacuum cleaners are better at cleaning carpets than cylinder vacuum cleaners because of the action of the  
20 rotating agitator brush. However, cylinder vacuum cleaners are better suited for above-floor cleaning and for cleaning in places where an upright cleaner cannot be used.

In order to provide a cleaner having the advantages of both upright and cylinder cleaners, it is known to provide an  
25 upright cleaner having an elongate flexible hose which can either be connected to the floor-engaging portion of the cleaner for conventional floor cleaning, or connected to an extension tube and/or cleaning tools for above-floor cleaning.

A disadvantage of this arrangement is that during  
30 conventional floor cleaning, the airflow thorough the cleaner is partially restricted by the elongate flexible hose, which is coiled for storage on the back of the cleaner. The coiled length of hose is also susceptible to blockage.

In order to overcome the above-mentioned problem, vacuum cleaners of the upright type are known which comprise a hose and a valve which can be actuated such that the suction is either applied to the hose for above-floor cleaning or to the floor-engaging portion of the cleaner for conventional floor cleaning.

European Patent No. 0 037 674 discloses an upright vacuum cleaner of the above-mentioned type comprising an elongate rigid tube, which is mounted vertically to the rear of the cleaner body and which forms a handle for manoeuvring the cleaner during conventional floor cleaning. In this configuration, the elongate rigid tube is enclosed within an elongate flexible suction hose which is retracted to its minimum length, and which is connected at its lower extremity to one of the inlet ports of a two-way valve, the outlet port of which is connected to the inlet of a cyclonic separator. In order to carry out above-floor cleaning, the rigid suction tube is withdrawn from the retracted suction hose, the lower end of the tube and the distal end of the hose having fittings which effect an airtight connection between the two conduits when the tube is withdrawn from the hose to its fullest extent. The action of withdrawing the rigid tube from its conventional floor cleaning position actuates the two-way valve, to divert the suction airstream from the floor-engaging portion of the cleaner to the hose.

It will be appreciated that during conventional floor cleaning, when the elongate rigid tube is stowed on the cleaner body, the user has to grasp the upper end of the elongate rigid tube to manoeuvre the cleaner. When the rigid tube is disconnected for above-floor cleaning, this upper end of the tube becomes the distal end of the tube. However, since the upper end of the elongate rigid tube needs to be ergonomically shaped to provide a handle for manoeuvring the cleaner, it is not practical to form the upper end of the tube of a shape which is instantly ready for above-floor cleaning when the



elongate rigid tube is disconnected. Accordingly, prior to using the cleaner in the above-floor cleaning mode, the user firstly has to locate and then fit a tool to the upper end of the tube. This procedure is time consuming and makes it  
5 difficult for the user to conveniently and quickly swap between floor and above-floor cleaning.

We have now devised a vacuum cleaner which can be used for both floor and above-floor cleaning and which alleviates the above-mentioned problems.

10 In accordance with this invention, there is provided a vacuum cleaner comprising:

a floor-engaging portion having a first air inlet on the underside thereof;

an upright portion pivotally connected at its lower end  
15 to said floor-engaging portion;

a handle upstanding from the upper end of said upright portion and having a first end and a second end, said first end of the handle being detachably engaged with a formation on said upright portion;

20 a rigid tubular duct extending along the handle between a second air inlet at said first end thereof and an outlet disposed remote from said first end; and

an elongate flexible hose having a first end and a second end, the first end of the hose being connected to said  
25 outlet on said handle, wherein the cross-sectional area of the rigid tubular duct extending along the handle increases substantially from said second air inlet at said first end of the handle towards said outlet disposed remote from said first end of said handle, the cross-sectional area of the rigid  
30 tubular duct at said first end of the handle being substantially uniform over an elongate region.

The elongate outer region at the first end of the handle thus acts to form a narrow above-floor cleaning tool, which is already connected in-situ ready for use, thereby

avoiding the need to connect a tool before above-floor cleaning can commence.

Preferably, the cross-sectional area of duct in the elongate region of the handle is 40%-60% less than the cross-sectional area of the duct adjacent said outlet of the handle.

Preferably, the duct in the elongate region of the handle comprises a major transverse axis which is at least 40% greater in length than its minor transverse axis lying perpendicular thereto. In this manner the so-called tool has a substantially flat configuration.

Preferably, said major transverse axis lies along a line which extends between the front and rear of the cleaner when said handle is engaged with the upright portion of the cleaner.

Preferably, the duct adjacent said outlet of the handle is substantially circular in section.

Preferably, the formation on the upright portion comprises a socket which is arranged to receive said elongate outer portion of the lower end of the handle.

Preferably, socket is arranged to conceal the first end of the handle and said second air inlet thereon. In this manner, the so-called tool of the handle is concealed from view when the cleaner is being used for floor cleaning.

Preferably, the cleaner comprises a valve having a first inlet port fluidly connected to said first air inlet in said floor-engaging portion, a second inlet port fluidly connected to the second end of said elongate flexible hose, an outlet port connected to a dust separation device and means for selectively connecting said valve outlet port to either said first or said second valve inlet ports.

In use, to use the cleaner for floor cleaning, the valve is configured to apply suction to the first air inlet in the floor-engaging portion. The handle is then used to propel and guide the cleaner over the surface being cleaned.



To use the cleaner for above-floor cleaning, the handle is simply detached and the valve configured to apply suction to the second air inlet at the first end of the handle via the elongate flexible hose.

5 Preferably, the valve comprises an actuator arranged to configure the valve to connect said second air inlet to said dust separation device when the handle is removed from upright portion and to connect said first air inlet to said dust separation device when the handle is engaged with said upright  
10 portion.

Preferably the handle comprises an elongate tubular member of plastics material, which is preferably closed at the second end of the handle is and is preferably shaped to provide a hand grip which can be grasped by the user.

15 Whist the so-called tool provided by the elongate region at the first end of the handle is always attached to the cleaner so that it is ready to use, means are preferably provided to allow a portion of the lower end of the handle to be removed, in order to enable any blockages in the duct to be  
20 cleared.

Preferably, the handle is retained in the socket against a resilient bias by a catch. When the catch is released, the handle is biased out of the socket to a position where it is conveniently offered to the user for above-floor  
25 cleaning. Simultaneously, the valve is preferably actuated to divert the suction from the first air inlet on the underside of the floor-engaging portion to the second air inlet on the handle.

An embodiment of this invention will now be described  
30 by way of example only and with reference to the accompanying drawings, in which:

Figure 1 is a side view of an upright vacuum cleaner in accordance with this invention, configured for floor cleaning;

Figure 2 is a side view of the vacuum cleaner of Figure  
35 1, configured for above-floor cleaning;

Figure 3 is a longitudinal sectional view through the handle of the vacuum cleaner of Figure 1;

Figure 4 is a sectional view along the line IV-IV of Figure 3;

5 Figure 5 is a sectional view along the line V-V of Figure 3; and

Figure 6 is a schematic diagram to illustrate the principle of operation of a valve mechanism of the vacuum cleaner of Figure 1.

10 Referring to Figure 1 of the drawings, there is shown an upright vacuum cleaner comprising an upright portion 10 pivotally connected at its lower end to a floor-engaging portion 11 for partial rotation forwardly and rearwardly about an axis which extends transverse the cleaner. The upright  
15 portion 10 encloses a motor/fan unit and comprises a detachable handle 12 at its upper end for manoeuvring the cleaner over the surface being cleaned. A first suction inlet 13 is provided on the underside of the floor-engaging portion 11 and a motor-driven rotating agitator brush mounted (not shown) is  
20 mounted across the inlet 13.

A cylindrical separation unit 14 for separating dirt and dust from the airflow is mounted to the front of the upright portion 10 of the cleaner. A further handle 15 for carrying the cleaner is provided on top of the upright portion.  
25 10 of the cleaner.

Referring to Figure 2 of the drawings, the detachable handle 12 is removably received in a vertical socket 16 formed in the rear of the upright portion 10 of the cleaner. The upper portion of the wall of the socket 16 comprises a catch 17 which  
30 engages a barb 18 on the side wall of the handle 12 to retain the latter in the socket 16.

Referring to Figure 3 the drawings, the handle 12 is formed of three main generally tubular portions 19, 20, 21 of plastics material connected end-to-end. The first tubular  
35 portion 19 is disposed at the upper end of the handle 12 and

is shaped to provide a hand grip 17 which the user can grasp when manoeuvring the cleaner during floor cleaning. An end cap 22 is fitted to the free end on the upper tubular portion 19 to provide an upper end wall of the handle 12.

5           The lower end of the upper tubular portion 19 is engaged to the upper end of an elongate central tubular portion 20 having generally parallel sides. The lower end of the central tubular portion 20 is detachably engaged to the upper end of lower tubular portion 20 by fastenings 23.

10           An airflow duct 24 extends along the handle 12 from a second suction inlet 28, provided at the lower end of the handle 12, to an air outlet 25 provided in the side wall of the of the central portion 20 of the handle 12, at a point adjacent the upper end thereof. The outlet 25 is coupled to the distal  
15 end of an elongate flexible hose 26, which extends from the upright portion 10 of the cleaner, as shown in Figure 2. A cranked tubular insert member 27 is disposed inside the handle 12 to direct air flowing up the handle 12 to the outlet 25 and to prevent any airflow into the upper portion 19 of the handle  
20 12 which forms the handgrip.

Referring to Figures 4 and 5 of the drawings, the duct 24 in the central portion 20 of the handle is substantially circular in cross-section and has a cross-sectional area substantially equal to the cross-sectional area of the hose 26.  
25 and the other flow ducts leading to the motor/fan unit via the separation unit 14. However, the cross-sectional area of the duct 24 reduces along the tubular lower portion 21 of the handle 12 from its upper end towards the second suction inlet 28 at the lower end thereof. Typically, the cross-sectional  
30 area of the duct 12 in the handle may reduce from 1800-2200 mm<sup>2</sup> adjacent the outlet 25 to 450-650mm<sup>2</sup> at the second suction inlet 28. Furthermore, the lower tubular portion 21 comprises an elongate region adjacent the second suction inlet 28 having a substantially uniform width, which is substantially less than  
35 the width the central tubular portion 20. Typically, the width

of this region may be 60 to 75% less than the width of the central tubular portion 20. The width of the lower tubular portion 21 at the second suction inlet 28 is also substantially less than the orthogonal dimension by a factor of say 40 to 5 60%.

In this manner, the region at the lower end of the handle 12 provides a narrow so-called crevice tool which is normally attached to the handle, even when the latter is mounted to the cleaner, as shown in Figure 1, for conventional 10 floor cleaning. Whist the so-called crevice tool provided by the elongate region at the lower end of the handle 12 is always attached to the cleaner so that it is ready to use, the fastenings 23 can be disconnected to allow the lower portion 21 of the handle 12 to be removed, in order to enable any 15 blockages in the duct 24 to be cleared.

Separate tools, such as brushes and heads (not shown) may be carried on the cleaner for attachment to the crevice tool at the lower end of the handle 12.

Referring to Figure 6 of the drawings, when the cleaner 20 is being used for conventional floor cleaning and the handle 12 is fitted in the socket 15, as shown in Figure 1, the lower end of the handle 12 abuts a member 30, which is disposed at the bottom of the socket 15 and which is biased upwardly by springs eg 31 mounted on respective lateral sides of the 25 socket. The underside of the member 30 is connected to a valve 32 by a linkage 33.

The valve 32 comprises a body 34 having a first inlet duct 35 connected to the first suction inlet 13 on the floor-engaging portion 11 of the cleaner and a second inlet 30 duct 36 connected to the proximal end of the elongate flexible hose 26. An outlet duct 37 is rotatably mounted to the body 34 and comprises one end provided with a seal 29 for selective alignment with one of said inlet ducts 35, 36. The opposite end of the of the outlet duct 37 of the valve 23 is connected via 35 a flexible hose (not shown) to the motor/fan unit via the

separation unit 14, which separates dirt and dust from the airflow.

The rotary outlet duct 37 is connected to the linkage 33, such that the outlet duct 37 of the valve 32 is connected to the inlet duct 35 when the member 30 is pushed down by the lower end of the handle 12 as the latter is fitted to the cleaner for conventional floor cleaning. The handle 12 is retained in the socket 15 against the resilient bias by the catch 18 on the wall of the socket, which engages the barb 19 on the handle 12.

In order to use the cleaner for above-floor cleaning, the user merely has to release the catch 17, which allows the handle 12 to move a small distance upwardly out of the socket 15 under the spring bias to the member 30. This upward movement of the member 30 actuates the linkage 33, which rotates the outlet duct 37 to a position where it is connected to the inlet duct 36 to which the hose 26 is connected.

Once released by the catch 17, the handle 12 is immediately and conveniently ready for use as a tool for above-floor cleaning without the user having to manually divert the suction or fit cleaning tools. The hose 26 is of the long-stretch type, which is able to extend to in excess of six times its retracted length. The arrangement of the cleaner is ideally suited to stair cleaning, since the body of the cleaner can be left at the top or bottom of the stairs whilst the tool is used to clean the stairs.

The cleaner is easily reverted to floor cleaning by replacing the handle 12 in the socket 15 against the spring bias, until the catch 17 on the wall of the socket 15 engages the barb 19 on the handle 12, whereupon the suction is diverted from the hose 20 to the suction inlet in the floor-engaging portion 11 of the cleaner.

A vacuum cleaner in accordance with this invention is uncomplicated in construction yet can be simply and

conveniently converted between floor and above-floor cleaning use.



1/4




FIG. 1

2/4




FIG. 2

3/4





FIG 4




FIG 5

FIG 3

4/4




FIG. 6